

COMSOL Multiphysics® Simulation of Heat Generation From Hydrogen/Deuterium Loading of Nickel Alloy Nanoparticles

G. Miley¹, A. Osouf¹, B. Stunkard¹, T. Patel¹, E. Ziehm¹, A. Krishnamurthy¹, K. J. Kim¹

¹University of Illinois, Champaign, IL, USA

Abstract

A key issue for the development of a LENR power unit involves the measurement and energy output of the reaction. Our team is currently studying a gas loaded nanoparticle-type cluster power unit [1] which pressurizes various nanoparticle alloys with either deuterium or hydrogen. The principal elements in the various nanoparticle alloys are Nickel, Palladium and Zirconium, with each alloy containing different percentages of each.

The research is currently focused on determining excess energy output that can be attributed to LENR (Low Energy Nuclear Reactions) [1]. Due to the current experimental setup, only the exterior temperatures of the reactor chamber are routinely measured during the experiments. In one chamber however, a centreline temperature can be monitored. The initial peaks in temperature during the pressurization show significant power production. Using the exterior temperature data to determine an accurate evaluation of energy output is complicated. The complexity results from the various heat transfer between the reactor, piping, insulation and natural convection.

Therefore, a COMSOL Multiphysics® model of the whole apparatus has been created in order to simulate the loadings. The final geometrical model provides an early time calculation of a reference cooling simulation. This reference cooling simulation is then compared to actual cooling data to ensure that the model is accurate. Then for pressurization experiments, the LENR input power in the model will be varied to match the actual external temperatures. This match will then provide a measure of the actual LENR power produced in the experiment. Our team is also working on improving the rapidity of the simulation process which is currently time consuming. When the various pressurization experiments are reproduced on the software, the model will also allow the team to determine any correlations between powder composition, gas type and heat output.

Our presentation will provide data on the process used to create the reference cooling curves. Then we will discuss the results of the simulations and explain the reliability of the values of power and energy production that is predicted. We will then conclude by comparing the different nanoparticle composition effects.

Reference

[1] Tapan Patel et al., Recent results from gas loaded nanoparticle-type cluster power units. International Conference ICCF 18, University of Missouri, Columbia (2013, July).